HAND DRYERS




ML_ECOSLENDER05_SS

EcoSlender Slimline Automatic Operation Hand Dryer in Satin Stainless Steel

Specification

1.2mm #304 Satin Stainless Steel Contemporary curved design Patented high-flow dual air outlets Brush Type Dual Ball Bearings 16,000-29,000 RPM 95°C auto reset overload 240V, 50Hz, 1000W, 4.17A 68.9dB - 74.3dB (Adjustable)
Patented high-flow dual air outlets Brush Type Dual Ball Bearings 16,000-29,000 RPM 95°C auto reset overload 240V, 50Hz, 1000W, 4.17A
Dual Ball Bearings 16,000-29,000 RPM 95°C auto reset overload 240V, 50Hz, 1000W, 4.17A
68 9dB - 74 3dB (Adjustable)
00.74b - 74.54b (Adjustable)
Less than 15 seconds
IP24
325W - 500W (Adjustable)
ON/OFF Heating Options 85°C auto-resetting thermostat 142°C auto reset safety cut off
Speed: 45.5m/s - 70m/s (Adjustable)
Temp: Ambient +25°C
60-sec power cut off, auto reset
Infrared Automatic, Self Adjusting 170mm+/-20mm Blue LED indicates operation/range
2 SS theft-resistant hex drive screws (hex key supplied)
3.8kg
275.5mmW x 216mmH x 100mmD
5 Year Warranty (3 Years Parts and Labour + 2 Years Parts only)
* The unit can be hard wired by an electrician or used with the cord and plug provided. * This unit is accessible compliant when installed in accordance with AS1428.1. guidelines

















Downloads & Resources

Care & Maintenance
Installation instructions
Mounting template
Revit
Promotions
Associated Videos
Stainless Steel Cleaning & Maintenance
Discover the Difference

TroubleShooting your Metlam Australia Hand Dryer

The photographs and line drawings of the products presented above are representational only.

Metlam Australia Pty Ltd reserves the right to, and from time to time, make changes and improvements in design and dimensions.